EZ Swap Specifications:

Model	MRK-102FD
Device Space	5.25” Half height device x 1
Interface	40 Pin IDE
Data Transfer Rate	133MB/Sec (support ATA133)
Power ON / OFF	Key lock
Cooling Fan	40(W) x 40(H) x 10(D) mm Ball Bearing x 1
DC Socket Number	1
Temperature Setting	20.0°C ~ 80.0°(50.0°C Default)
Temperature Display	10.0°C~ 90.0°C
Accuracy of Temperature	± 3.0°C
HDD Access Display	Display on LCD screen
Alarm function	Display on LCD Screen (50.0°C Alarm Default)
Alarm Disable	Manual setting
Fan Failure Display	Alarm and display on LCD screen
Overheating Display	Alarm and display on LCD screen
Signal Out	Temperature over heat signal Out (High)
	Fan Fail Signal Out (High)
HUTR Display	0-999 day 23 hr
HDD Condition Display	Master or Slave
Master / Slave Setting	Four-Segment Dip Switch
Master / Slave Display	Display on LCD screen
Flat Cable	PVC
Material	Plastic and Aluminum alloy
Dimension (W x H x D)	148.0X42.0X235.5mm
Weight	750g

Vantec Thermal Technologies, Inc.
Address: 43185 Osgood Rd.
Fremont, CA 94539
TEL: 510-668-0368
E-mail: support@vantecusa.com